



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: Fractional Explosion Proof Motors

Frame : 56
 Output : 0.33 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1725 rpm
 Slip : 4.17 %
 Voltage : 208-230/460 V
 Rated current : 1.30-1.18/0.588 A
 Locked rotor current : 7.88/3.94 A
 Locked rotor current (I_L/I_n) : 6.7
 No-load current : 1.00/0.500 A
 Full load torque : 0.991 lb.ft
 Locked rotor torque : 310 %
 Breakdown torque : 430 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 8 s (hot)
 Service factor : 1.00
 Duty cycle : S1
 Ambient temperature : -20°C - +50°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 21 lb
 Moment of inertia : 0.01400 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.69	77.3
75%	0.60	74.0
50%	0.48	67.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.3318XS3E56

Performed by

Checked