



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase: Fractional Explosion Proof Motors

Frame : 56  
 Output : 0.33 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1725 rpm  
 Slip : 4.17 %  
 Voltage : 208-230/460 V  
 Rated current : 1.30-1.18/0.588 A  
 Locked rotor current : 7.88/3.94 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.7  
 No-load current : 1.00/0.500 A  
 Full load torque : 0.991 lb.ft  
 Locked rotor torque : 310 %  
 Breakdown torque : 430 %  
 Design : A  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 8 s (hot)  
 Service factor : 1.00  
 Duty cycle : S1  
 Ambient temperature : -20°C - +50°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 21 lb  
 Moment of inertia : 0.01400 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.69	77.3
75%	0.60	74.0
50%	0.48	67.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.3318XS3E56C

Performed by

Checked