



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : W56
Output : 0.33 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3490 rpm
Slip : 3.06 %
Voltage : 115/208-230 V
Rated current : 5.20/2.87-2.60 A
Locked rotor current : 36.4/18.2 A
Locked rotor current (I_L/I_n) : 7.0
No-load current : 3.80/1.90 A
Full load torque : 0.490 lb.ft
Locked rotor torque : 290 %
Breakdown torque : 290 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 8 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 19 lb
Moment of inertia : 0.01898 sq.ft.lb
Noise level : 66 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.76	54.0
Regreasing interval	---	---	75%	0.69	50.0
Grease amount	---	---	50%	0.61	42.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.3336ES1BW56-S

Performed by

Checked