



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Jet Pump - NEMA 56 : Three-Phase - Keyed - TEFC (IP55)

Frame : B56C  
 Output : 0.33 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3465 rpm  
 Slip : 3.75 %  
 Voltage : 208-230/460 V  
 Rated current : 1.22-1.20/0.600 A  
 Locked rotor current : 9.60/4.80 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.0  
 No-load current : 0.780/0.390 A  
 Full load torque : 0.493 lb.ft  
 Locked rotor torque : 500 %  
 Breakdown torque : 400 %  
 Design : A  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.15 (1.00 at 208V)  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 23 lb  
 Moment of inertia : 0.02373 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 2RS	6202 2RS	100%	0.78	66.0
Regreasing interval	---	---	75%	0.71	61.0
Grease amount	---	---	50%	0.61	52.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.3336ES3EJPR56C

Performed by

Checked