



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump - NEMA 56 : Three-Phase - Threaded - TEFC (IP55)

Frame : B56J
 Output : 0.33 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3465 rpm
 Slip : 3.75 %
 Voltage : 208-230/460 V
 Rated current : 1.22-1.20/0.600 A
 Locked rotor current : 9.60/4.80 A
 Locked rotor current (I_L/I_n) : 8.0
 No-load current : 0.780/0.390 A
 Full load torque : 0.493 lb.ft
 Locked rotor torque : 500 %
 Breakdown torque : 400 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.15 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 21 lb
 Moment of inertia : 0.02373 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 2RS	6202 2RS	100%	0.78	66.0
Regreasing interval	---	---	75%	0.71	61.0
Grease amount	---	---	50%	0.61	52.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.3336ES3EJPR56J

Performed by

Checked