



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : C56
Output : 0.33 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3480 rpm
Slip : 3.33 %
Voltage : 115/208-230 V
Rated current : 5.70/2.60-2.85 A
Locked rotor current : 33.6/16.8 A
Locked rotor current (I_L/I_n) : 5.9
No-load current : 4.20/2.10 A
Full load torque : 0.491 lb.ft
Locked rotor torque : 380 %
Breakdown torque : 300 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.35 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 21 lb
Moment of inertia : 0.01898 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.65	57.6
75%	0.59	54.1
50%	0.49	46.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.3336OS1BC56CFL

Performed by

Checked