



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump - NEMA 56 : Single-Phase - Threaded - ODP (IP21)

Frame : W56
 Output : 0.33 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3470 rpm
 Slip : 3.61 %
 Voltage : 115/208-230 V
 Rated current : 5.80/2.60-2.90 A
 Locked rotor current : 32.5/16.2 A
 Locked rotor current (I_L/I_n) : 5.6
 No-load current : 4.40/2.20 A
 Full load torque : 0.493 lb.ft
 Locked rotor torque : 340 %
 Breakdown torque : 300 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.75 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 22 lb
 Moment of inertia : 0.01898 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6203 2RS	6202 2RS
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.66	58.0
75%	0.60	54.0
50%	0.52	46.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.3336OS1BJP56J

Performed by

Checked