



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

### DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Jet Pump: Three-Phase - W01 (Rolled Steel) - Keyed - ODP - Standard Efficiency

Frame : 56C  
Output : 0.33 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3515 rpm  
Slip : 2.36 %  
Voltage : 208-230/460 V  
Rated current : 1.38-1.25/0.624 A  
Locked rotor current : 8.36/4.18 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.7  
No-load current : 0.900/0.450 A  
Full load torque : 0.486 lb.ft  
Locked rotor torque : 240 %  
Breakdown torque : 320 %  
Design : A  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 38 s (hot)  
Service factor : 1.75  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : ODP  
Approximate weight : 16 lb  
Moment of inertia : 0.03892 sq.ft.lb  
Noise level : 62 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.74	68.0
75%	0.65	66.0
50%	0.54	57.5

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #.3336OS3EJPR56C-S

Performed by

Checked