



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Jet Pump - NEMA 56 : Three-Phase - Threaded - ODP (IP21)

Frame : A56  
 Output : 0.33 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3500 rpm  
 Slip : 2.78 %  
 Voltage : 208-230/460 V  
 Rated current : 1.34-1.40/0.698 A  
 Locked rotor current : 7.96/3.98 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.7  
 No-load current : 1.10/0.550 A  
 Full load torque : 0.488 lb.ft  
 Locked rotor torque : 260 %  
 Breakdown torque : 320 %  
 Design : A  
 Insulation class : B  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.75 (1.00 at 208V)  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP21  
 Approximate weight : 23 lb  
 Moment of inertia : 0.01661 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.
Bearings	6203 2RS	6202 2RS
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.72	63.0
75%	0.64	57.0
50%	0.54	48.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.3336OS3EJPR56J

Performed by

Checked