



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56
 Output : 0.5 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1170 rpm
 Slip : 2.50 %
 Voltage : 115/208-230 V
 Rated current : 6.40/3.54-3.20 A
 Locked rotor current : 42.2/21.1 A
 Locked rotor current (I_L/I_n) : 6.6
 No-load current : 4.40/2.20 A
 Full load torque : 2.21 lb.ft
 Locked rotor torque : 240 %
 Breakdown torque : 260 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 18 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 31 lb
 Moment of inertia : 0.12411 sq.ft.lb
 Noise level : 54 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.72	67.0
Regreasing interval	---	---	75%	0.67	63.0
Grease amount	---	---	50%	0.58	54.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.5012ES1B56C-S

Performed by

Checked