



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET

### Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Single-Phase : NEMA 56 TEFC

Frame : D56  
Output : 0.5 HP  
Frequency : 60 Hz  
Poles : 6  
Full load speed : 1180 rpm  
Slip : 1.67 %  
Voltage : 115/208-230 V  
Rated current : 7.20/3.50-3.60 A  
Locked rotor current : 41.0/20.5 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.7  
No-load current : 5.60/2.80 A  
Full load torque : 2.20 lb.ft  
Locked rotor torque : 250 %  
Breakdown torque : 300 %  
Design : ---  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.15 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 38 lb  
Moment of inertia : 0.14285 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6202 ZZ	100%	0.63	71.0
Regreasing interval	---	---	75%	0.55	67.0
Grease amount	---	---	50%	0.47	58.0

#### Notes:

Downloaded from <http://dealerselectric.com>  
Generated for Model #.5012ES1BD56CFL

Performed by

Checked