



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - TEFC

Frame : B56
Output : 0.5 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1160 rpm
Slip : 3.33 %
Voltage : 208-230/460 V
Rated current : 2.40-2.60/1.30 A
Locked rotor current : 13.8/6.89 A
Locked rotor current (I_L/I_n) : 5.3
No-load current : 2.30/1.15 A
Full load torque : 2.23 lb.ft
Locked rotor torque : 350 %
Breakdown torque : 400 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 28 lb
Moment of inertia : 0.10631 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.51	70.0
75%	0.43	66.0
50%	0.34	59.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.5012ES3EB56C

Performed by

Checked