



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : B56
Output : 0.5 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1140 rpm
Slip : 5.00 %
Voltage : 208-230/460 V
Rated current : 2.00-2.00/1.00 A
Locked rotor current : 9.00/4.50 A
Locked rotor current (I_L/I_n) : 4.5
No-load current : 1.60/0.800 A
Full load torque : 2.27 lb.ft
Locked rotor torque : 250 %
Breakdown torque : 270 %
Design : A
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.25 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 26 lb
Moment of inertia : 0.07119 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.65	68.0
75%	0.55	67.5
50%	0.44	59.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.5012OS3EB56C

Performed by

Checked