



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - ODP - Premium Efficiency (DOE)

Frame : 56
 Output : 0.5 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1155 rpm
 Slip : 3.75 %
 Voltage : 208-230/460 V
 Rated current : 2.06-1.87/0.934 A
 Locked rotor current : 9.53/4.76 A
 Locked rotor current (I_L/I_n) : 5.1
 No-load current : 1.50/0.750 A
 Full load torque : 2.24 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 260 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 28 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 21 lb
 Moment of inertia : 0.08875 sq.ft.lb
 Noise level : 50 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.66	75.3
75%	0.56	74.0
50%	0.43	68.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.5012OT3E56C-S

Performed by

Checked