



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 56 TEFC

Frame : B56
Output : 0.5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1750 rpm
Slip : 2.78 %
Voltage : 115/208-230 V
Rated current : 7.40/3.60-3.70 A
Locked rotor current : 42.9/21.5 A
Locked rotor current (I_L/I_n) : 5.8
No-load current : 5.60/2.80 A
Full load torque : 1.48 lb.ft
Locked rotor torque : 290 %
Breakdown torque : 270 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 24 lb
Moment of inertia : 0.08044 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.65	66.5
Regreasing interval	---	---	75%	0.57	64.0
Grease amount	---	---	50%	0.46	56.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.5018ES1BB56CFL

Performed by

Checked