



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : W56
 Output : 0.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1730 rpm
 Slip : 3.89 %
 Voltage : 115/208-230 V
 Rated current : 8.00/4.42-4.00 A
 Locked rotor current : 45.6/22.8 A
 Locked rotor current (I_L/I_n) : 5.7
 No-load current : 6.60/3.30 A
 Full load torque : 1.50 lb.ft
 Locked rotor torque : 320 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.15 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 21 lb
 Moment of inertia : 0.04793 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.63	64.0
75%	0.54	59.0
50%	0.44	52.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.5018ES1BW56CFL-S

Performed by

Checked