



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Farm Duty Motors : TEFC (IP55) - Single-Phase

Frame : B56
 Output : 0.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1750 rpm
 Slip : 2.78 %
 Voltage : 115/230 V
 Rated current : 7.40/3.70 A
 Locked rotor current : 42.9/21.5 A
 Locked rotor current (I_L/I_n) : 5.8
 No-load current : 5.60/2.80 A
 Full load torque : 1.48 lb.ft
 Locked rotor torque : 290 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 24 lb
 Moment of inertia : 0.08044 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.65	66.5
75%	0.57	64.0
50%	0.46	56.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.5018ES1RFDB56

Performed by

Checked