



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - TEFC

Frame : B56
Output : 0.5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1750 rpm
Slip : 2.78 %
Voltage : 208-230/460 V
Rated current : 1.65-1.60/0.800 A
Locked rotor current : 12.3/6.16 A
Locked rotor current (I_L/I_n) : 7.7
No-load current : 1.00/0.500 A
Full load torque : 1.48 lb.ft
Locked rotor torque : 280 %
Breakdown torque : 370 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 10 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 29 lb
Moment of inertia : 0.10655 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.74	77.0
75%	0.65	75.5
50%	0.53	70.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.5018ES3EB56C

Performed by

Checked