



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET

### Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Single-Phase : NEMA 48 & 56 ODP - Split Phase

Frame : C48  
Output : 0.5 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1730 rpm  
Slip : 3.89 %  
Voltage : 115/208-230 V  
Rated current : 8.00/4.00-4.00 A  
Locked rotor current : 48.0/24.0 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.0  
No-load current : 6.00/3.00 A  
Full load torque : 1.50 lb.ft  
Locked rotor torque : 130 %  
Breakdown torque : 220 %  
Design : ---  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 6 s (hot)  
Service factor : 1.25 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP21  
Approximate weight : 26 lb  
Moment of inertia : 0.04817 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.63	63.5
Regreasing interval	---	---	75%	0.54	61.0
Grease amount	---	---	50%	0.44	54.5

#### Notes:

Downloaded from <http://dealerselectric.com>  
Generated for Model #.5018OS1BSPC48C

Performed by

Checked