



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - ODP - Standard Efficiency

Frame : 56
 Output : 0.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1755 rpm
 Slip : 2.50 %
 Voltage : 208-230/460 V
 Rated current : 2.16-1.95/0.977 A
 Locked rotor current : 11.7/5.86 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 1.60/0.800 A
 Full load torque : 1.48 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 290 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 23 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 17 lb
 Moment of inertia : 0.04532 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.66	72.0
Regreasing interval	---	---	75%	0.56	70.0
Grease amount	---	---	50%	0.43	64.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.5018OS3E56CFL-S

Performed by

Checked