



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : A56
Output : 0.5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1730 rpm
Slip : 3.89 %
Voltage : 208-230/460 V
Rated current : 1.81-1.82/0.909 A
Locked rotor current : 10.5/5.27 A
Locked rotor current (I_L/I_n) : 5.8
No-load current : 1.59/0.797 A
Full load torque : 1.50 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 280 %
Design : A
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.25 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 23 lb
Moment of inertia : 0.07095 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.73	70.0
75%	0.62	66.0
50%	0.51	62.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.5018OS3EA56C

Performed by

Checked