



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Single Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56  
 Output : 0.75 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1170 rpm  
 Slip : 2.50 %  
 Voltage : 115/208-230 V  
 Rated current : 9.40/5.20-4.70 A  
 Locked rotor current : 60.2/30.1 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.4  
 No-load current : 6.00/3.00 A  
 Full load torque : 3.32 lb.ft  
 Locked rotor torque : 220 %  
 Breakdown torque : 240 %  
 Design : ---  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 35 lb  
 Moment of inertia : 0.15970 sq.ft.lb  
 Noise level : 54 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.73	70.0
Regreasing interval	---	---	75%	0.67	67.0
Grease amount	---	---	50%	0.58	59.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.7512ES1B56CFL-S

Performed by

Checked