



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 56 TEFC

Frame : F56H
Output : 0.75 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1170 rpm
Slip : 2.50 %
Voltage : 115/208-230 V
Rated current : 10.0/4.80-5.00 A
Locked rotor current : 54.0/27.0 A
Locked rotor current (I_L/I_n) : 5.4
No-load current : 7.40/3.70 A
Full load torque : 3.32 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 260 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 42 lb
Moment of inertia : 0.17774 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.68	71.0
75%	0.59	67.0
50%	0.49	59.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.7512ES1BF56CFL

Performed by

Checked