



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56H
 Output : 0.75 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1155 rpm
 Slip : 3.75 %
 Voltage : 208-230/460 V
 Rated current : 2.96-2.68/1.34 A
 Locked rotor current : 15.5/7.77 A
 Locked rotor current (I_L/I_n) : 5.8
 No-load current : 1.94/0.971 A
 Full load torque : 3.36 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 300 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 21 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 30 lb
 Moment of inertia : 0.13313 sq.ft.lb
 Noise level : 50 dB(A)

	D.E.	N.D.E.
Bearings	6204 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.68	75.5
75%	0.59	74.0
50%	0.46	70.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.7512ES3E56C-S

Performed by

Checked