



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - TEFC

Frame : D56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1160 rpm
Slip : 3.33 %
Voltage : 208-230/460 V
Rated current : 2.88-2.95/1.48 A
Locked rotor current : 17.4/8.70 A
Locked rotor current (I_L/I_n) : 5.9
No-load current : 2.25/1.13 A
Full load torque : 3.35 lb.ft
Locked rotor torque : 300 %
Breakdown torque : 350 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 35 lb
Moment of inertia : 0.14214 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.58	81.5
75%	0.49	80.0
50%	0.38	75.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.7512ES3ED56C

Performed by

Checked