



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56
 Output : 0.75 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1745 rpm
 Slip : 3.06 %
 Voltage : 115/208-230 V
 Rated current : 10.6/5.86-5.30 A
 Locked rotor current : 67.8/33.9 A
 Locked rotor current (I_L/I_n) : 6.4
 No-load current : 8.00/4.00 A
 Full load torque : 2.23 lb.ft
 Locked rotor torque : 300 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 29 lb
 Moment of inertia : 0.07783 sq.ft.lb
 Noise level : 54 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.67	68.5
75%	0.58	65.0
50%	0.47	57.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.7518ES1B56CFL-S

Performed by

Checked