



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : B56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1735 rpm
Slip : 3.61 %
Voltage : 208-230/460 V
Rated current : 2.65-2.66/1.33 A
Locked rotor current : 16.8/8.38 A
Locked rotor current (I_L/I_n) : 6.3
No-load current : 2.00/1.00 A
Full load torque : 2.24 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 280 %
Design : A
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 10 s (hot)
Service factor : 1.25 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 24 lb
Moment of inertia : 0.06455 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.72	72.0
75%	0.63	70.0
50%	0.50	64.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.7518OS3EB56

Performed by

Checked