



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : B56  
Output : 0.75 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1735 rpm  
Slip : 3.61 %  
Voltage : 208-230/460 V  
Rated current : 2.65-2.66/1.33 A  
Locked rotor current : 16.8/8.38 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.3  
No-load current : 2.00/1.00 A  
Full load torque : 2.24 lb.ft  
Locked rotor torque : 240 %  
Breakdown torque : 280 %  
Design : A  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 10 s (hot)  
Service factor : 1.25 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP21  
Approximate weight : 24 lb  
Moment of inertia : 0.06455 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.72	72.0
75%	0.63	70.0
50%	0.50	64.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #.7518OS3EB56C

Performed by

Checked