



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET

### Single-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Single Phase: W01 (Rolled Steel) - ODP - Premium Efficiency (DOE)

Frame : 56  
Output : 0.75 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1750 rpm  
Slip : 2.78 %  
Voltage : 115/208-230 V  
Rated current : 6.80/3.76-3.40 A  
Locked rotor current : 54.4/27.2 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.0  
No-load current : 2.80/1.40 A  
Full load torque : 2.22 lb.ft  
Locked rotor torque : 260 %  
Breakdown torque : 250 %  
Design : ---  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 20 s (hot)  
Service factor : 1.25  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : ODP  
Approximate weight : 31 lb  
Moment of inertia : 0.09729 sq.ft.lb  
Noise level : 52 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.86	81.8
Regreasing interval	---	---	75%	0.82	79.0
Grease amount	---	---	50%	0.74	74.0

#### Notes:

Downloaded from <http://dealerselectric.com>  
Generated for Model #.7518OT1B56-S

Performed by

Checked