



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase: Fractional Explosion Proof Motors

Frame : 56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1725 rpm
Slip : 4.17 %
Voltage : 115/208-230 V
Rated current : 10.4/5.20 A
Locked rotor current : 52.0/26.0 A
Locked rotor current (I_L/I_n) : 5.0
No-load current : 7.20/3.60 A
Full load torque : 2.25 lb.ft
Locked rotor torque : 330 %
Breakdown torque : 260 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 11 s (hot)
Service factor : 1.00
Duty cycle : S1
Ambient temperature : -20°C - +50°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 31 lb
Moment of inertia : 0.02681 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6203 ZZ	100%	0.70	69.8
Regreasing interval	---	---	75%	0.62	67.0
Grease amount	---	---	50%	0.51	60.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #.7518XS1B56

Performed by

Checked