



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 56 TEFC

Frame : B56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3490 rpm
Slip : 3.06 %
Voltage : 115/208-230 V
Rated current : 10.4/5.00-5.20 A
Locked rotor current : 65.5/32.8 A
Locked rotor current (I_L/I_n) : 6.3
No-load current : 7.60/3.80 A
Full load torque : 1.11 lb.ft
Locked rotor torque : 300 %
Breakdown torque : 290 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 26 lb
Moment of inertia : 0.03963 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.72	64.0
Regreasing interval	---	---	75%	0.64	60.0
Grease amount	---	---	50%	0.54	52.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #.7536ES1BB56C

Performed by

Checked