



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : B56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3525 rpm
Slip : 2.08 %
Voltage : 115/208-230 V
Rated current : 10.5/5.00-5.25 A
Locked rotor current : 63.0/31.5 A
Locked rotor current (I_l/I_n) : 6.0
No-load current : 8.30/4.15 A
Full load torque : 1.10 lb.ft
Locked rotor torque : 250 %
Breakdown torque : 280 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.25 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 28 lb
Moment of inertia : 0.03322 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6203 ZZ	100%	0.68	67.2
Regreasing interval	---	---	75%	0.61	64.2
Grease amount	---	---	50%	0.52	56.5

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #.7536OS1BB56C

Performed by

Checked