



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single Phase: W01 (Rolled Steel) - ODP - Premium Efficiency (DOE)

Frame : 56
Output : 0.75 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3510 rpm
Slip : 2.50 %
Voltage : 115/208-230 V
Rated current : 6.80/3.76-3.40 A
Locked rotor current : 58.5/29.2 A
Locked rotor current (I_L/I_n) : 8.6
No-load current : 2.40/1.20 A
Full load torque : 1.11 lb.ft
Locked rotor torque : 300 %
Breakdown torque : 300 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 18 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : ODP
Approximate weight : 25 lb
Moment of inertia : 0.04343 sq.ft.lb
Noise level : 58 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.93	76.2
Regreasing interval	---	---	75%	0.92	71.0
Grease amount	---	---	50%	0.88	64.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #.7536OT1B56-S

Performed by

Checked