



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Brake Motors : Three-Phase - High Efficiency

Frame : 145T
Output : 1 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1155 rpm
Slip : 3.75 %
Voltage : 230/460 V
Rated current : 3.40/1.70 A
Locked rotor current : 23.1/11.6 A
Locked rotor current (I_L/I_n) : 6.8
No-load current : 2.60/1.30 A
Full load torque : 4.49 lb.ft
Locked rotor torque : 260 %
Breakdown torque : 300 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 22 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 49 lb
Moment of inertia : 0.13289 sq.ft.lb
Noise level : 49 dB(A)

	D.E.	N.D.E.
Bearings	6205 ZZ	6205 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.69	80.0
75%	0.60	80.0
50%	0.48	75.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00112EP3EBM145T

Performed by

Checked