



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W01 (Rolled Steel) General Purpose ODP

Frame : 143/5T
Output : 1 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1760 rpm
Slip : 2.22 %
Voltage : 208-230/460 V
Rated current : 3.34-3.02/1.51 A
Locked rotor current : 24.2/12.1 A
Locked rotor current (I_L/I_n) : 8.0
No-load current : 1.92/0.958 A
Full load torque : 2.94 lb.ft
Locked rotor torque : 290 %
Breakdown torque : 360 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 22 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : ODP
Approximate weight : 34 lb
Moment of inertia : 0.11011 sq.ft.lb
Noise level : 52 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6205 ZZ	6203 ZZ	100%	0.73	85.5
Regreasing interval	---	---	75%	0.65	84.0
Grease amount	---	---	50%	0.51	81.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00118OT3E143T-SG

Performed by

Checked