



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W01 (Rolled Steel) - TEFC - Premium Efficiency (DOE)

Frame : W56
 Output : 1 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3435 rpm
 Slip : 4.58 %
 Voltage : 208-230/460 V
 Rated current : 3.32-3.00/1.50 A
 Locked rotor current : 26.4/13.2 A
 Locked rotor current (I_L/I_n) : 8.8
 No-load current : 1.60/0.798 A
 Full load torque : 1.51 lb.ft
 Locked rotor torque : 360 %
 Breakdown torque : 380 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.15 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 21 lb
 Moment of inertia : 0.02539 sq.ft.lb
 Noise level : 65 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.80	78.5
75%	0.75	77.0
50%	0.63	74.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00136ET3E56C-S

Performed by

Checked