



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W21 IE3 IEC Tru-Metric - TEFC (IP55) Multi-Mounting Aluminum Frame

Frame : 80
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3450 rpm
 Slip : 4.17 %
 Voltage : 460 V
 Rated current : 2.03 A
 Locked rotor current : 16.2 A
 Locked rotor current (I_L/I_n) : 8.0
 No-load current : 1.06 A
 Full load torque : 2.25 lb.ft
 Locked rotor torque : 530 %
 Breakdown torque : 520 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 27 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 28 lb
 Moment of inertia : 0.03560 sq.ft.lb
 Noise level : 59 dB(A)

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.81	84.0
75%	0.74	81.5
50%	0.62	78.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00136ET3WAL80

Performed by

Checked