



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 High Efficiency

Frame : 143T  
Output : 1.5 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3455 rpm  
Slip : 4.03 %  
Voltage : 230/460 V  
Rated current : 3.98/1.99 A  
Locked rotor current : 27.1/13.5 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.8  
No-load current : 1.80/0.900 A  
Full load torque : 2.25 lb.ft  
Locked rotor torque : 250 %  
Breakdown torque : 300 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 13 s (hot)  
Service factor : 1.25  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 39 lb  
Moment of inertia : 0.03702 sq.ft.lb  
Noise level : 68 dB(A)

	D.E.	N.D.E.
Bearings	6205 ZZ	6204 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.84	82.5
75%	0.78	82.5
50%	0.68	78.5

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00156EP3ER143TC-W22

Performed by

Checked