



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56  
 Output : 1.5 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3460 rpm  
 Slip : 3.89 %  
 Voltage : 208-230/460 V  
 Rated current : 4.40-3.98/1.99 A  
 Locked rotor current : 28.7/14.3 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.2  
 No-load current : 1.63/0.815 A  
 Full load torque : 2.25 lb.ft  
 Locked rotor torque : 240 %  
 Breakdown torque : 270 %  
 Design : A  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 12 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 26 lb  
 Moment of inertia : 0.07712 sq.ft.lb  
 Noise level : 68 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6202 ZZ	100%	0.90	77.0
Regreasing interval	---	---	75%	0.85	75.5
Grease amount	---	---	50%	0.76	72.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00156ES3E56CFL-S

Performed by

Checked