



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

### DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Three-Phase : NEMA 56 Frames - TEFC

Frame : B56  
Output : 1.5 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3440 rpm  
Slip : 4.44 %  
Voltage : 208-230/460 V  
Rated current : 4.25-3.90/1.95 A  
Locked rotor current : 33.2/16.6 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.5  
No-load current : 1.72/0.860 A  
Full load torque : 2.26 lb.ft  
Locked rotor torque : 450 %  
Breakdown torque : 350 %  
Design : A  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 15 s (hot)  
Service factor : 1.15 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 34 lb  
Moment of inertia : 0.05102 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.88	82.5
75%	0.82	80.0
50%	0.72	76.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00156ES3EB56C

Performed by

Checked