



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Jet Pump - NEMA 56 : Three-Phase - Keyed - TEFC (IP55)

Frame : B56C
Output : 1.5 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3440 rpm
Slip : 4.44 %
Voltage : 208-230/460 V
Rated current : 4.25-3.90/1.95 A
Locked rotor current : 33.2/16.6 A
Locked rotor current (I_L/I_n) : 8.5
No-load current : 1.72/0.860 A
Full load torque : 2.26 lb.ft
Locked rotor torque : 450 %
Breakdown torque : 350 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.15 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 34 lb
Moment of inertia : 0.05102 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 2RS	6202 2RS
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.88	82.5
75%	0.82	80.0
50%	0.72	76.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00156ES3EJPR56C

Performed by

Checked