



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Three-Phase - "JM" Type - ODP - High Efficiency

Frame : E143/5JM
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3430 rpm
 Slip : 4.72 %
 Voltage : 230/460 V
 Rated current : 3.90/1.95 A
 Locked rotor current : 34.3/17.2 A
 Locked rotor current (I_L/I_n) : 8.8
 No-load current : 1.90/0.950 A
 Full load torque : 2.27 lb.ft
 Locked rotor torque : 420 %
 Breakdown torque : 340 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 33 lb
 Moment of inertia : 0.04366 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6206 ZZ	6204 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.86	84.0
75%	0.80	84.0
50%	0.69	81.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00156OP3E143JM

Performed by

Checked