



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - ODP - High Efficiency

Frame : 143/5JP  
 Output : 1.5 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3495 rpm  
 Slip : 2.92 %  
 Voltage : 208-230/460 V  
 Rated current : 4.16-3.76/1.88 A  
 Locked rotor current : 29.3/14.7 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.8  
 No-load current : 1.61/0.804 A  
 Full load torque : 2.22 lb.ft  
 Locked rotor torque : 240 %  
 Breakdown torque : 320 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 22 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : ODP  
 Approximate weight : 29 lb  
 Moment of inertia : 0.03583 sq.ft.lb  
 Noise level : 62 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6206 ZZ	6203 ZZ	100%	0.89	82.5
Regreasing interval	---	---	75%	0.84	82.5
Grease amount	---	---	50%	0.73	81.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #00156OP3E143JP-S

Performed by

Checked