



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump - NEMA 56 : Three-Phase - Threaded - ODP (IP21)

Frame : D56
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3400 rpm
 Slip : 5.56 %
 Voltage : 208-230/460 V
 Rated current : 4.50-4.26/2.13 A
 Locked rotor current : 25.5/12.8 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 2.10/1.05 A
 Full load torque : 2.29 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 230 %
 Design : A
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.30 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 32 lb
 Moment of inertia : 0.03037 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.
Bearings	6204 2RS	6202 2RS
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.87	76.0
75%	0.81	76.0
50%	0.69	74.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00156OS3EJP56J

Performed by

Checked