



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Jet Pump: Three-Phase - W01 (Rolled Steel) - Threaded - ODP - Standard
 Efficiency

Frame : 56J
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3460 rpm
 Slip : 3.89 %
 Voltage : 575 V
 Rated current : 1.69 A
 Locked rotor current : 11.5 A
 Locked rotor current (I_L/I_n) : 6.8
 No-load current : 0.880 A
 Full load torque : 2.25 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 17 s (hot)
 Service factor : 1.30
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 23 lb
 Moment of inertia : 0.06478 sq.ft.lb
 Noise level : 62 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.85	77.0
Regreasing interval	---	---	75%	0.78	77.0
Grease amount	---	---	50%	0.65	74.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00156OS3HJP56J-S

Performed by

Checked