



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - TEFC - Standard Efficiency

Frame : 56H
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1750 rpm
 Slip : 2.78 %
 Voltage : 575 V
 Rated current : 1.78 A
 Locked rotor current : 13.4 A
 Locked rotor current (I_L/I_n) : 7.5
 No-load current : 1.20 A
 Full load torque : 4.44 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 300 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 9 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 31 lb
 Moment of inertia : 0.10370 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6202 ZZ	100%	0.76	81.5
Regreasing interval	---	---	75%	0.67	80.0
Grease amount	---	---	50%	0.54	77.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00158ES3H56C-S

Performed by

Checked