



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : F56H
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1730 rpm
 Slip : 3.89 %
 Voltage : 115/208-230 V
 Rated current : 18.5/9.27 A
 Locked rotor current : 111/55.6 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 12.8/6.38 A
 Full load torque : 4.49 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 240 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : ---
 Service factor : 1.15 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 45 lb
 Moment of inertia : 0.19554 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6204 ZZ	6203 ZZ	100%	0.71	72.9
Regreasing interval	---	---	75%	0.62	72.0
Grease amount	---	---	50%	0.50	67.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00158OS1BF56C

Performed by

Checked