



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - ODP - Standard Efficiency

Frame : 56H
 Output : 1.5 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1745 rpm
 Slip : 3.06 %
 Voltage : 208-230/460 V
 Rated current : 5.09-4.60/2.30 A
 Locked rotor current : 31.7/15.9 A
 Locked rotor current (I_L/I_n) : 6.9
 No-load current : 3.20/1.60 A
 Full load torque : 4.45 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 280 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 10 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 28 lb
 Moment of inertia : 0.09065 sq.ft.lb
 Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6204 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.75	80.0
75%	0.65	78.5
50%	0.51	75.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #00158OS3E56C-S

Performed by

Checked