



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

### DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W01 (Rolled Steel) General Purpose ODP

Frame : 143/5T  
Output : 1.5 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1760 rpm  
Slip : 2.22 %  
Voltage : 208-230/460 V  
Rated current : 4.58-4.14/2.07 A  
Locked rotor current : 36.0/18.0 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 8.7  
No-load current : 2.40/1.20 A  
Full load torque : 4.42 lb.ft  
Locked rotor torque : 280 %  
Breakdown torque : 330 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 15 s (hot)  
Service factor : 1.15  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : ODP  
Approximate weight : 42 lb  
Moment of inertia : 0.14262 sq.ft.lb  
Noise level : 52 dB(A)

	D.E.	N.D.E.
Bearings	6205 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.77	86.5
75%	0.69	86.5
50%	0.56	84.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #00158OT3E145T-SG

Performed by

Checked