



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase: Fractional Explosion Proof Motors

Frame : 56H
Output : 1.5 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1725 rpm
Slip : 4.17 %
Voltage : 208-230/460 V
Rated current : 4.29-3.88/1.94 A
Locked rotor current : 29.1/14.6 A
Locked rotor current (I_L/I_n) : 7.5
No-load current : 2.00/1.00 A
Full load torque : 4.51 lb.ft
Locked rotor torque : 250 %
Breakdown torque : 350 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.00
Duty cycle : S1
Ambient temperature : -20°C - +50°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 39 lb
Moment of inertia : 0.00973 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.84	84.7
75%	0.78	84.0
50%	0.67	81.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #00158XS3E56HC

Performed by

Checked